

Profi-Allzweckband Pro-All-Purpose-Tape

Beschreibung

Allzweck-Klebeband Sorte 402 besteht aus einem strapazierfähigen, wasserdichten und kunststoffbeschichteten Gewebe, einseitig klebend. Es hat eine sehr hohe Anfangshaftung und Klebkraft. Beständig gegen Wasser, Öl, mechanische Beschädigungen und viele chemische Einflüsse.

Anwendung

Dieses Band kann für alle denkbaren Zwecke eingesetzt werden. Ihr zuverlässiger Helfer für Abdekarbeiten, Reparaturarbeiten an Schläuchen und Rohren etc. Reparieren von Löchern und Rissen in Planen, Markisen, Segeln etc. wasserdichtes Versiegeln von Behältern, sicheres Verpacken von Transportgütern.

Product Description

All-Purpose Tape Type 402 consists of a heavy duty, water-proof and plastics coated fabric, which is adhesive on one side. It has a very high adhesion. Resistant against water, oil, mechanical damage and many chemical influences.

Application

This tape can be used for any kind of application. Your solid assistant for covering work sandblasting, repairing of tubes and pipes etc., repairing of cracks and wholes in tarpaulin, awnings, sails, etc., sealing of containers to make them waterproof, to secure packaging of goods in transport.

Technische Daten

Träger	PE-beschichtetes Gewebe
Gesamtdicke	165 µ
Dehnung bis Bruch	30 %
Klebkraft auf Stahl	8 N/cm
Zugfestigkeit	30 N/cm
Klebstoff	Synthetischer Kautschuk
Temperaturbeständigkeit	bis 75° C
Kerndurchmesser	76 mm
Farbe	weiß, silber, schwarz
Länge	50 m

Technical Data

Backing	PE-coated cloth
Total thickness	165 µ
Elongation at break	30 %
Adhesion on steel	8 N/cm
Tensile strength	30 N/cm
Adhesive	synthetic rubber
Temperature resistance	up to 75° C
Core diameter	76 mm
Colour	white, silver, black
Length	50 m

Verpackungseinheiten

Bandbreite in mm	Rollen pro Karton
38 (silber)	32
48 (weiß, silber, schwarz)	24

Packaging

Roll width mm	Rolls per carton
38 (silver)	32
48 (white, silver, black)	24

The information is based on our current knowledge and experience. No guarantee of specific properties or the suitability of the product for a particular purpose can be inferred from our information. All descriptions, drawings, photographs, data, ratios, weights, etc. contained herein are subject to change without notice and do not constitute the contractually agreed quality of the product. Technical changes, dimensional changes, printing errors, and mistakes are reserved.